

[general]

static = yes ; These two lines prevent the command-line interface  
writeprotect = yes ; from overwriting the config file. Leave them here.

[globals]

HOMENPA = 301 ; change this to your Area Code  
NODE = 500001 ; change this to your node number  
NODE1 = 500002 ; change this to your node number  
NODE2 = 500003 ; change this to your node number  
NODE3= 1999 ; change this to your LOCAL node number

[default]

exten => i,1,Hangup

[radio-secure]

exten => \${NODE},1,rpt,\${NODE}  
exten => \${NODE1},1,rpt,\${NODE1}  
exten => \${NODE2},1,rpt,\${NODE2}  
exten => \${NODE3},1,rpt,\${NODE3}

[iaxrpt]

exten => \${NODE},1,rpt(\${NODE}|X) ; entered from iaxrpt in iax.conf  
; NODE is the Name field in iaxrpt  
; Info: The X option passed to the Rpt application  
; disables the normal security checks.  
; Because incoming connections are validated in iax.conf,  
; and we don't know where the user will be coming from in advance,  
; the X option is required.

exten => \${NODE1},1,rpt(\${NODE1}|X)  
exten => \${NODE2},1,rpt(\${NODE2}|X)

[iax-client]

; for IAX VIOP clients.

exten => \${NODE},1,Ringing  
exten => \${NODE},n,Wait(3)  
exten => \${NODE},n,Answer  
exten => \${NODE},n,Set(NODENUM=\${CALLERID(number)})  
exten => \${NODE},n,Playback(rpt/node|noanswer)  
exten => \${NODE},n,SayDigits(\${EXTEN})  
exten => \${NODE},n,Set(CALLERID(num)=0)  
exten => \${NODE},n,Rpt,\${NODE}|P|\${CALLERID(name)}  
exten => \${NODE},n,Hangup  
exten => \${NODE},n(hangit),Answer  
exten => \${NODE},n(hangit),Wait(1)  
exten => \${NODE},n(hangit),Hangup

[iax-client2]

; for IAX VIOP clients.

exten => \${NODE1},1,Ringing  
exten => \${NODE1},n,Wait(3)  
exten => \${NODE1},n,Answer  
exten => \${NODE1},n,Set(NODENUM=\${CALLERID(number)})  
exten => \${NODE1},n,Playback(rpt/node|noanswer)

```
exten => ${NODE1},n,SayDigits(${EXTEN})
exten => ${NODE1},n,Set(CALLERID(num)=0)
exten => ${NODE1},n,Rpt,${NODE1}|P|${CALLERID(name)}
exten => ${NODE1},n,Hangup
exten => ${NODE1},n(hangit),Answer
exten => ${NODE1},n(hangit),Wait(1)
exten => ${NODE1},n(hangit),Hangup
```

**[iax-client3]** ; for IAX VIOP clients.

```
exten => ${NODE2},1,Ringing
exten => ${NODE2},n,Wait(3)
exten => ${NODE2},n,Answer
exten => ${NODE2},n,Set(NODENUM=${CALLERID(number)})
exten => ${NODE2},n,Playback(rpt/node|noanswer)
exten => ${NODE2},n,SayDigits(${EXTEN})
exten => ${NODE2},n,Set(CALLERID(num)=0)
exten => ${NODE2},n,Rpt,${NODE2}|P|${CALLERID(name)}
exten => ${NODE2},n,Hangup
exten => ${NODE2},n(hangit),Answer
exten => ${NODE2},n(hangit),Wait(1)
exten => ${NODE2},n(hangit),Hangup
```

