

register = 500001:ASLpassword@register.allstarlink.org ; This must be changed to your node number, password  
register = 500002:ASLpassword@register.allstarlink.org ; This must be changed to your node number, password  
register = 500003:ASLpassword@register.allstarlink.org ; This must be changed to your node number, password

```
[iaxclient] ; Connect from iax client (Zoiper...)  
type = friend ; Notice type here is friend <-----  
context = iax-client ; Context to jump to in extensions.conf  
auth = md5  
secret = 12345678 ; Your password  
host = dynamic  
disallow = all  
allow = ulaw  
allow = adpcm  
allow = gsm  
transfer = no
```

```
[500001] ; Connect from iax client (Zoiper...)  
type = friend ; Notice type here is friend <-----  
context = iax-client ; Context to jump to in extensions.conf  
auth = md5  
secret = 12345678 ; Your password  
host = dynamic  
disallow = all  
allow = ulaw  
allow = adpcm  
allow = gsm  
transfer = no
```

```
[500002] ; Connect from iax client (Zoiper...)  
type = friend ; Notice type here is friend <-----  
context = iax-client2 ; Context to jump to in extensions.conf  
auth = md5  
secret = 12345678 ; Your password  
host = dynamic  
disallow = all  
allow = ulaw  
allow = adpcm  
allow = gsm  
transfer = no
```

```
[500003] ; Connect from iax client (Zoiper...)  
type = friend ; Notice type here is friend <-----  
context = iax-client2 ; Context to jump to in extensions.conf  
auth = md5  
secret = 12345678 ; Your password  
host = dynamic  
disallow = all  
allow = ulaw  
allow = adpcm  
allow = gsm  
transfer = no
```

